

260 Series

Benchtop DC Insulation Tester

■ **The 260 DC Insulation tester** performs DC dielectric withstand (hipot) tests. These bench top instruments are designed to test electrical system apparatus and components in an efficient and reliable manner.



FEATURES

- Rack mountable**
- Interlock provision**
- Adjustable over current protection**
- Overload light**
- Zero start interlock**
- Output shorting relay**
- Triple range voltage meter**
- Triple range current meter**

BENEFITS

Safe and easy benchtop operation

NIST traceable calibration

Accurate measurements independent of load and line variations

Automatic discharge of test object

APPLICATIONS

- Wire and cable
- Capacitors
- Coils and inductors
- High Voltage Tubes

TECHNICAL SPECIFICATION

Model Number	260-*	
System Output (V)	0-60 kV	
Voltage Meter	0-12/30/60kV	
Current Meter	0-0.1/1/10mA	
Overload	1-11mA	
Dimensions (W x H x D)	21 x 15 x 19.5 in (53 x 38 x 79 cm)	
Weight	Net	90 lbs (41kg)
	Shipping	105 lbs (47.6 kg)
Input Voltage & Frequency	* In the model number, designate 'A' for 115V/60Hz input or 'B' for 220V/50Hz input	
Included Items	QTY 1: High Voltage RG8/U, alligator clip, 25ft (7.6m)	
	QTY 1: Grounding stud with screw connection on chassis of controller	
	User's Manual	
	Calibration Certificate	

OPTIONAL EQUIPMENT & ACCESSORIES

Part Number	Description
HHDA13-280	Grounding Stick, 120kV Max Voltage
SPK1-260	Spare Parts Kit for 260
EXT-WARRANTY	One year extended warranty



*HHDA13-280 Grounding Stick
(pictured above)*

OFFICES:

Europe
Haefely Test AG
Birsstrasse 300
4052 Basel
Switzerland

☎ + 41 61 373 4111
☎ + 41 61 373 4912
✉ sales@haefely.com

China

Haefely Test AG Representative Beijing Office
8-1-602, Fortune Street
No. 67, Chaoyang Road, Chaoyang District
Beijing, China 100025

☎ +86 10 8578 8099
☎ +86 10 8578 9908
✉ sales@haefely.com.cn

North America

Hipotronics, Inc.
1650 Route 22 N
Brewster, NY 10509
United States

☎ +1 845 279 3644
☎ +1 845 279 2467
✉ sales@hipotronics.com